

PDFVCE



Choose the version that fits your needs	PDF Version	Desktop Test Engine	Online Test Engine
Latest and Up-to-Date exam dumps with real exam questions answers.	✓	✓	✓
Get 12-Months free updates without any extra charges.	✓	✓	✓
Experience same exam environment before appearing in the certification exam.	✗	✓	✓
100% exam passing guarantee in the first attempt.	✓	✓	✓
20% discount on more than one license and 30% discount on 5+ license purchases.	✗	✓	✓
100% secure purchase on SSL.	✓	✓	✓
Completely private purchase without sharing your personal info with anyone.	✓	✓	✓

<http://www.pdfvce.com>

Highly Efficiently Exam Tool and Effective Exam Practice Materials

Exam : HP0-086

Title : HP Bladesystem p-Class Solutions 1

Vendors : HP

Version : DEMO

NO.1 What is the recommended environment for using high-voltage PDUs?

- A.when using single-phase power and 3U power enclosures
- B.when using facility DC power with a fully-populated 42U rack
- C.when using 3U power enclosures with the non-enhanced server blade enclosures
- D.when using a large number of server blades that place a high load on the power bus
- E.when using the enhanced server blade enclosure in a redundant power configuration

Correct:D

NO.2 You have an enhanced server blade enclosure fully populated with ProLiant BL35p server

blades. You connect to the bottom server blade in server bay 1 using the local I/O cable, and want

to enable the Static IP Bay Configuration feature to automatically assign IP addresses to all server

blade iLOs in the enclosure. However, the Static IP Bay Configuration option is not available.

Why?

- A.A DHCP server exists on your network.
- B.You are not connected to the first server blade in the first bay.
- C.The management module on the back of the server blade enclosure is incorrectly configured.
- D.The power enclosure and the server blade enclosure management ports are not cabled or cabled incorrectly.

Correct:B

NO.3 You are configuring an enhanced server blade enclosure that is fully populated with BL35p

server blades to boot Windows Server 2003 from a single MSA1000 storage solution. What is the

minimum number of logical units (LUNs) you must create on the MSA1000?

- A.2
- B.4
- C.8
- D.16

Correct:D

NO.4 You have an enhanced server blade enclosure connected to a single 3U power enclosure. Only

side A of the server blade enclosure is connected to the power enclosure. Which server blade enclosure bays receive DC power?

- A. bays 1 through 8
- B. bays 1 through 8, plus the interconnect bays
- C. bays 1 through 4, plus the interconnect bays
- D. bays 1 through 4, plus the interconnect bay on side A
- E. bays 5 through 8, plus the interconnect bay on side A

Correct: C

NO.5 Which UPS supports the p-Class infrastructure and is 3U high?

- A. HP R1500XR
- B. HP R3000XR
- C. HP R5500XR
- D. HP R12000XR

Correct: C

NO.6 When accessing the iLO BL p-Class tab, you receive the "Unable to collect rack data" error

message. Why? (Select two.)

- A. At least one server blade iLO is not configured.
- B. You have not yet licensed all server blade iLOs.
- C. At least one management module has mismatched firmware.
- D. A DHCP server exists on the network and conflicts with the Static IP Bay Configuration feature.
- E. At least one power enclosure or server blade enclosure does not meet the minimum firmware requirements.

Correct: C E

NO.7 How do the HP ProLiant BL p-Class server blades support network attached storage (NAS)?

(Select two.)

- A. through the embedded network adapters
- B. through optional multifunction network adapters
- C. through optional mezzanine or balcony host bus adapters
- D. through the additional NIC ports on the front of the interconnect switches
- E. through the additional NIC ports on the back of the interconnect switches

Correct:A B

NO.8 Which HP server blade uses a Fibre Channel loop to combine two internal SAN port connections to a single external physical connection?

- A.ProLiant BL35p
- B.ProLiant BL45p
- C.ProLiant BL20p G2
- D.ProLiant BL20p G3

Correct:A

NO.9 How many server-facing Fibre Channel ports are included in the Brocade 4Gb SAN switch for the HP BladeSystem?

- A.4
- B.8
- C.12
- D.16

Correct:B

NO.10 When must the load-balancing cable be installed?

- A.when one or more power enclosure pairs are installed in a rack
- B.when an odd number of power enclosures are installed in a rack
- C.when a three-phase power enclosure is connected to the original server blade enclosure
- D.when one power enclosure provides redundant power to the original server blade enclosure

Correct:A

NO.11 What is the default user name and password for the GbE2 Interconnect Switch administrator account?

- A.user name: , password: hp
- B.user name: admin, password: admin
- C.user name: admin, password: compaq
- D.user name: Administrator, password: password

Correct:B

NO.12 What is the default administrator account username and password for the Brocade 4Gb SAN

Switch?

A.admin/admin

B.admin/password

C.administrator/

D.administrator/password

Correct:B

NO.13 You are creating a VLAN on a GbE2 Interconnect Switch. This VLAN must include the crosslink

ports. Which ports must you include?

A.ports 1 and 2

B.ports 3 and 4

C.ports 15 and 16

D.ports 17 and 18

Correct:D

NO.14 What is the maximum combination of power and enhanced server blade enclosures that can be

connected to a mini bus bar?

A.1 power and 2 server blade enclosures

B.1 power and 3 server blade enclosures

C.2 power and 2 server blade enclosures

D.2 power and 3 server blade enclosures

Correct:D

NO.15 Which power distribution option requires the dual power input kit for power redundancy?

A.mini bus bar

B.power bus box

C.scalable bus bar

D.facility DC power

Correct:A

NO.16 You have a fully populated enhanced server blade enclosure. You connect your laptop with a

crossover cable to the RJ-45 port of the local I/O cable and insert the other end of the local I/O

cable into the local I/O port in the front of blade 3. You then set your laptop to the IP address

192.168.1.2 and the subnet mask 255.255.255.0. When you enter http://192.168.1.1 in the Microsoft

Internet Explorer address field, you receive the "Page not found" error message. Why?

A.The default IP address of the iLO is 192.168.0.1.

B.The iLO Advanced firmware is older than version 1.64 and must be upgraded first.

C.The local I/O cable is already a crossover cable, thus another crossover cable is not required.

D.The power enclosure and the server blade enclosure management ports are not cabled or cabled

incorrectly.

Correct:C

NO.17 Which configuration requires two power zones to be enabled on the power enclosure management modules?

A.any configuration that mixes a single phase and three-phase power

B.full 42U rack with four 3U power enclosures connected by mini bus bars

C.full 42U rack with four 3U power enclosures connected by scalable bus bars

D.any configuration that has two or more 3U power enclosures connected to the facility DC power

Correct:B

NO.18 Which HP SIM plug-in component enables scanning for and patching of network vulnerabilities?

A.PIM

B.PMP

C.VMM

D.VPM

Correct:D

NO.19 You connect to the iLO of a ProLiant BL20p G2 server blade through the Ethernet port. The iLO

web interface does not display the BL p-Class tab. Why?

A.The BL p-Class tab is disabled by default.

B.The iLO firmware is older than version 1.64.

C.The iLO Advanced is not licensed in the HP BladeSystem Integrated Management.

D.The BL p-Class tab is only available when accessing the iLO through the local I/O port.

Correct:B

NO.20 What is the recommended environment for using high-voltage modular power distribution units (PDUs)?

A.when using 1U power enclosures

B.when using 3U, single-phase power enclosures

C.when using 3U, three-phase power enclosures and redundant power

D.when using 3U, three-phase power enclosures and non-enhanced server blade enclosures

Correct:A